

Manufacturer	KIOTI	Branson	Case Farmall 55	Challenger	John Deere	John Deere	Kubota	Massey Ferg	McCormick	Montana	New Holland
Model	DK55 Cab 4WD	5530 cab MFD	Cab MFD	315B Cab 4WD	4520 Cab 4WD	5225 Cab MFWD	M5040 Cab 4WD	1655 SS Cab 4WD	CT65U Cab 4WD	5740C 4WD	T2410 Cab FWD
Drive Type	DK55 Cab 4WD	5530 cab MFD	Cab MFD	315B Cab 4WD	4520 Cab 4WD	5225 Cab MFWD	M5040 Cab 4WD	1655 SS Cab 4WD	CT65U Cab 4WD	5740C 4WD	T2410 Cab FWD
<b>Engine</b>											
Type	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	5 Cyl Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	54	55	55	58	53.1	56	50.5	55.4	57	57	55
PTO HP	45.2	47	46	45	45.5	45	45	43	50	NP	47
Displacement Cu.In.	134.1	139.5	135.2	201	148.9	186	186	180.4	NP	203.3	135.2
Fuel Capacity Gal.	18	24	13.5	29	13.8	25	29.1	13.2	15.85	13.5	13.5
<b>Drive Train</b>											
Clutch	Dry Single	Dry Single	Dry	NP	Wet Multi	Dry	Dry	Wet Multi	Dry Single	NP	Dry Disc
Transmission	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle Power Rev	Syn. Shuttle	Syn. Shuttle	Power Shuttle	Mech. Shuttle	Syn. Shuttle	Syn. Shuttle
Speeds	12F12R	24F24R	12F12R	12F12R	12F12R	9F3R	8F8R	12F12R	16F16R	16F16R	12F12R
Differential Lock	STD	STD	STD	STD	STD	STD	n/a	STD	STD	STD	STD
Brake Type	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Multi Disc	Wet Multi Disc	Wet Multi Disc	Wet Disc
PTO Type	Live	Independent	Independent	Independent	Independent	Independent	Live-Indep.	Independent	Independent	Independent	Independent
Rear (RPM)	540/1000 OPT	540/680/1000	540	540	540	540	540	540	NP	540	540
Mid (RPM)	NP	NP	NP	NP	2100 OPT	NP	N/A	NA	NP	NP	NP
<b>Hydraulic System</b>											
Pump	Gear Tandem	Open Center	Gear	Gear	Dual Gear	Dual Gear	NP	Open Center	NP	NP	Gear
Total Hydraulic Flow (gpm)	9.88	NP	16.95	15.8	17.1	19.4	11	17.7	14.1	13.9	16.9
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1 & 2	Cat. 1 & 2	Cat. 1	Cat. 1 & 2	Cat. 1	Cat. 1	Cat. 2	Cat. 1	Cat. 1 & 2
Lift Capacity at 24" behind lift point Lbs	2,654	NP	3,465	5,500 at link end	2,500	3,374	3,307	3,483 at hitch point	3,860 at ball end	3,527 at ball end	3,465
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power
<b>Dimensions</b>											
Overall Length IN.	130.5	143.6	137.3	148	128.2	142	135.6	132.7	NP	142	137.3
Overall Width IN.	69.3	74	64.4	76	90	71	73.2	67.3	NP	68.6	71.6
Overall Height IN.	101.5	100	90.8	102.5	97.2	94	98.2	90.2	NP	97	88.25
Wheel Base IN.	75.6	80	74.8	82.7	71.5	85.8	83.1	76	NP	81.7	74.8
Turning Radius FT.	9.6	NP	NP	NP	9.8	10.2	11.8	NP	NP	11.8	9.2
Weight with CAB Lbs.	5,180*	5,549	NP	7,716	4,345*	6,580*	3,968*	4,110*	5,225	5,556	5,220*
<b>Warranty</b>											
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	4 year limited	NP	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	NP	Full 24 month, additional 12 month Powertrain
<b>Notes</b>											
Notes	*wt. with Ag Tires		12x12 Power Shuttle option	OP 12F12R Power Shuttle	*Shipping weight	*Shipping weight	*Weight with ROPS not cab and Ag tires	*Shipping weight			*Shipping weight

N/A - Not Available

NP - Not Published

OPT - Optional

Competitive information contained in this document was obtained from various available sources including websites. As a result, KIOTI does not guarantee or warrant the accuracy of this information.

<b>Manufacturer</b>	<b>KIOTI</b>	<b>TYM</b>
<b>Model</b>	<b>DK55 Cab 4WD</b>	<b>T603 Cab 4WD</b>
<b>Drive Type</b>	<b>DK55 Cab 4WD</b>	<b>T603 Cab 4WD</b>
<b>Engine</b>		
Type	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	54	58
PTO HP	45.2	46.6
Displacement Cu.In.	134.1	135.2
Fuel Capacity Gal.	18	18.5
<b>Drive Train</b>		
Clutch	Dry Single	Dry Single
Transmission	Syn. Shuttle	Syn. Shuttle
Speeds	12F12R	24F24R
Differential Lock	STD	NP
Brake Type	Wet Disc	Wet Disc
PTO Type	Live	Independent
Rear (RPM)	540/1000 OPT	540/1000
Mid (RPM)	NP	N/A
<b>Hydraulic System</b>		
Pump	Gear Tandem	Dual Gear
Total Hydraulic Flow (gpm)	9.88	15.1
3-Point Hitch	Cat. 1	Cat. 2
Lift Capacity at 24" behind lift point Lbs	2,654	2,528
Steering	Hydro. Power	Hydro. Power
<b>Dimensions</b>		
Overall Length IN.	130.5	146.5
Overall Width IN.	69.3	71.5
Overall Height IN.	101.5	101.9*
Wheel Base IN.	75.6	83
Turning Radius FT.	9.6	9.2
Weight with CAB Lbs.	5,180*	5,380
<b>Warranty</b>		
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only)
<b>Notes</b>		
Notes	*wt. with Ag Tires	Height is for ROPS tractor

N/A - Not Available